


Description


- » 50 Nm torque
- » Open/close with FAILSAFE
- » 1.3" OLED display
- » User friendly push button control
- » Standardized interfaces (ISO 5211, DIN 3337)
- » Brushless high performance motor
- » Overload protection
- » Visual position indicator
- » Integrated heating resistor 3 W
- » End position feedback open/close



Technical data

Electrical data	Rated voltage	230V AC/DC	24V AC/DC
	Voltage range	95-265V AC / 100-300V DC	20-26V AC / 22-30V DC
	Power consumption	max. 40 W	
	Peak current	0,18A @5ms @AC230V	1,67A @5ms @DC24V
	Fuse	1A	4A
Functional data	Rated torque	50 Nm	
	Nominal angle	90 +/-2°	
	Max. angle	330° ±5°	
	Manual override	Currentless with allen key	
	Operating time (90°)	approx. 12 seconds	
	Operating mode	S3-75% (AC) S3-85% (DC) - loading ≤85% rated torque according to IEC60034-1-2017	
	Position indicator	Mechanical / Screen	
	Electricity safety level	Class I	Class III
	Protection class	IP67	
	Insulation resistance	100MΩ / 1500V DC	100MΩ / 500V DC
	Withstand voltage	1500V AC / 1 min	500V AC / 1 min
Operating conditions	Mounting position	Any mounting position	
	Temperature range	-20° ... +60°C	
	Storage temperature	-40° ... +80°C	
	Humidity	5 ... 95%, non-condensing	
	Shock resistance	≤5g	
	Vibration	10 ... 55 Hz / 1,5 mm double amplitude	

Dimension drawing



Ø Stem connection	Depth stem connection	ISO 5211	Weight
14 mm	15 mm	F05/F07	1,8kg

Materials


	<table><tr><td>1</td><td>Body</td><td>Heatproof ABS</td></tr><tr><td>2</td><td>Screws</td><td>304</td></tr><tr><td>3</td><td>Manual shaft</td><td>304</td></tr><tr><td>4</td><td>Oil seal</td><td>NBR</td></tr><tr><td>5</td><td>Label</td><td>PVC</td></tr></table>	1	Body	Heatproof ABS	2	Screws	304	3	Manual shaft	304	4	Oil seal	NBR	5	Label	PVC	<table><tr><td>6</td><td>Wrench fixation</td><td>Heatproof ABS</td></tr><tr><td>7</td><td>Hexagon wrench</td><td>Tool steel</td></tr><tr><td>8</td><td>Waterproof cable connector</td><td>Polyamide</td></tr><tr><td>9</td><td>Lid seal</td><td>NBR</td></tr></table>	6	Wrench fixation	Heatproof ABS	7	Hexagon wrench	Tool steel	8	Waterproof cable connector	Polyamide	9	Lid seal	NBR
1	Body	Heatproof ABS																											
2	Screws	304																											
3	Manual shaft	304																											
4	Oil seal	NBR																											
5	Label	PVC																											
6	Wrench fixation	Heatproof ABS																											
7	Hexagon wrench	Tool steel																											
8	Waterproof cable connector	Polyamide																											
9	Lid seal	NBR																											

Type code


ESA	TCR	05	C	-KT	0507	S	14	H	01
Housing Variant		Size/ Nominal torque		Version		Special function		ISO interfaces	
Stem connection		Stem connection dimension		Options		Supply voltage			
				00: Connection via terminal strip		L: 20 ... 26V AC / 22 ... 30V DC			
				01: with attached plug and mating plug for soldering		H: 95 ... 265V AC / 100 ... 300V DC			
				02-xm: with attached cable end with length „x“ in meters					

Electric connection


Connection variant open/closed 3-point



Connection variant open/closed 2-point



Connection variant 3-Positions



Connector pin assignment

