

Description


- » 20 Nm torque
- » Open/Close with highspeed
- » 1.3" OLED display
- » User friendly push button control
- » Standardized interfaces (ISO 5211, DIN 3337)
- » Brushless high performance motor
- » Overload protection
- » Visual position indicator
- » Integrated heating resistor 3 W
- » End position feedback open/close



Technical Data

Electrical data	Rated voltage	230V AC/DC	24V AC/DC
	Voltage range	95-265V AC / 100-300V DC	18-26V AC / 22-30V DC
	Power consumption	max. 25 W	max. 85 W
	Peak current	0,08A @5ms @AC230V	3,5A @5ms @DC24V
	Fuse	1A	8A
Functional data	Rated torque	15 Nm	20 Nm
	Nominal angle	90° ±2°	
	Max. angle	330° ±5°	
	Manual override	Currentless with allen key	
	Operating time (90°)	approx. 6 seconds	approx. 1 second
	Operating mode	S3-75% (AC) S3-85% (DC) - loading ≤85% rated torque according to IEC60034-1-2017	
	Position indicator	Mechanical / Screen	
	Electricity safety level	Class I	Class III
	Protection class	IP67	
	Insulation resistance	100MΩ / 1500V DC	100MΩ / 500V DC
	Withstand voltage	1500V AC / 1 min	500V AC / 1 min
Operating conditions	Mounting position	Any mounting position	
	Temperature range	-20° ... +60°C	
	Storage temperature	-40° ... +80°C	
	Humidity	5 ... 95%, non-condensing	
	Shock resistance	≤5g	
	Vibration	10 ... 55 Hz / 1,5 mm double amplitude	

Dimension drawing



Ø Stem connection	Depth stem connection	ISO 5211	Weight
14 mm	15 mm	F03/F05 F04 - 45° offset	0,62kg

Type code

ESA

TCR

02

C

H

030405

S

14

H

01

Housing Variant

Size/ Nominal torque

Version

Special function

ISO interfaces

Stem connection

Stem connection dimension

Options

Supply voltage

00: Connection via terminal strip

01: with attached plug and mating plug for soldering


02-xm: with attached cable end with length „x“ in meters

L: 20 ... 26V AC / 22 ... 30V DC


H: 95 ... 265V AC / 100 ... 300V DC

Electric connection


Connection variant open/closed 3-point



Connection variant open/closed 2-point



Connection variant 3-Positions



Connector pin assignment

